

UDOT Minimum Sampling and Testing Requirements

Revised January '07

Specification - Material: 02786 Open Graded Seal Coat

02786 Open Graded Seal Coat

Quality Assurance: Asphalt Binder Content

Reference: AASHTO T 308

Lot Size: Production Day

Frequency per Lot: Four

Point of Acceptance: Hot Plant

Sampling Reference: MOI 8-984

Report/Form:

Quality Assurance: Sieve Analysis

Reference: AASHTO T 30

Lot Size: Production Day

Frequency per Lot: Four

Point of Acceptance: Hot Plant

Sampling Reference: MOI 8-984

Report/Form:

Quality Assurance: Thickness

Reference: Verify with a depth probe

Lot Size:

Frequency per Lot:

Point of Acceptance:

Sampling Reference:

Report/Form:

<i>Specification - Material: 02786 Open Graded Seal Coat</i>
--

Quality Assurance: Smoothness

Reference: Standard Specification 01452

Lot Size:

Frequency per Lot:

Point of Acceptance:

Sampling Reference:

Report/Form:

Quality Assurance: Visual Acceptance of very small quantities of materials

Reference: Acceptance is limited to only material being furnished from sources found satisfactory under normal sampling and testing procedures.

Lot Size: Not to exceed 100 tons per day or 1000 tons per project

Frequency per Lot: One report for each day material is accepted

Point of Acceptance: Grade

Sampling Reference:

Report/Form: Visual Inspection Report
